



## 13" Automatic Trimmer Affordable and Efficient

The TR-1200 Autocutter is the perfect companion to the PL-1200HP Laminator. Utilizing the side slitters on board your laminator, the TR-1200 Autocutter trims the leading and trailing edges of the sheet giving you a completely finished product. Of course if you already have a laminator, the TR-1200 can run behind any lamination system to automatically and uniformly cut the leading and trailing edges of the sheets.

Don't be fooled by its small size, this system is loaded with features. The cutting margin can be adjusted to cut completely flush, leave a uniform border of film, or even negative cut into the laminated sheet. The leading and trailing edge cuts are independently controllable meaning you can flush cut the leading edge if desired while leaving a larger trailing edge margin. Larger margins are perfect for creating a tough laminated binding edge. Or flush trim for precision accuracy.

Accuracy to within .005 inch and perfect uniformity cut after a cut. Speeds up to 40 feet per minute and it is intuitive, meaning that the cutter learns the speed of your laminator and runs in time with it to keep web slack to a minimum.

You can also use the cutter off-line to trim already laminated webs. If you have more than one laminator this feature means you can laminate and trim with one system, laminate and allow the output to stack in a web from the second system. When you are done with the first system, just thread the already laminated web from the other system and let the cutter do the rest.

The integrated touch display of the system displays in either decimal or fractional measurements. It also keeps track of the number of sheets it has produced. The cutting mechanism is a rotary knife for clean accurate cuts sheet after sheet.

If you are currently hand trimming your sheets, this system will save you tremendous time and money while producing perfectly trimmed items sheet after sheet.



# TR-1200

# 13" Automatic Trimmer

**Affordable and Efficient**

## Features

Throughput Speeds in excess of 30ppm on 11 x 17 sheet  
Cuts 1.2 mil to 10 mil Laminate  
Digital Microprocessor Controlled  
Large LCD Touch Screen Display  
Intuitive User Adjustable Settings  
Precise Settings to .005  
Rotary Self-Sharpening Blade  
Magnetic Outfeed Guides

## Installed Specifications

Weight: 80  
Dimensions: Machine 30" x 20" x 12"  
Stand 29" x 16" x 7"

## Electrical Requirements

Volts: 120  
Operational: .4 Amps / 50 watts  
Power Saving, Standby: .1 Amps / 10 watts

## Operational Capacities

Max Designed Width: 13"  
Minimum Length: 4"  
Maximum Length : None  
Min / Max Margin: +/- .001" - 1"  
Min / Max Film Thickness: 1.2 mil / 10 mil  
Maximum Overall thickness: .050" (~3/64")

Model Number TR-1200

Made In The USA



www.drylam.com  
P: 888-633-1973  
F: 866-473-0534  
23220 W 84th St..  
Shawnee, KS 66227